



EPOXY STRIPPER

INTRODUCTION

This thixotropic product is a non-flammable stripper designed to facilitate the removal of the more resistant paint films which remain unaffected by most conventional strippers.

APPLICATION

Epoxy Stripper should either be applied liberally with a soft brush to give a thick wet film or the component immersed in a tank containing the stripper. After approximately ten minutes the paint film should then be easily removed by a light scraping.

FLASHPOINT

Flash point above 55oC. Tested to BS3900 Part A8.

PREPARATION

Should the stripped article require painting, all traces of Epoxy Stripper must be removed and the substrate must be thoroughly clean and free from contaminants, corrosion and grease.

Note: A detergent solution or white spirit may be used for the removal of any residual Epoxy Stripper.

SAFETY AND HANDLING PRECAUTIONS

Eyes and skin should always be protected when using this product. Chemical splash goggles and PVC gauntlets are normally suitable. Before use, refer to our Individual Safety Information Sheet. Smoking should be prohibited not only in areas where this material is stored or used by in any other area where vapours are likely to accumulate.

DISPOSAL

Dispose of in accordance with local authority requirements.



PRODUCT FAMILIES

The following products are referred to in this data sheet.

PRODUCT NAME	PRODUCT NUMBER
EPOXY STRIPPER	MP1000-5

Whilst every endeavour has been made to ensure that the information given in this data sheet is correct, PMD Chemicals Limited gives no warranty, express or implied, relating to the use or performance of this product.