



T WIPES 8

Water Based Quality

INTRODUCTION

These wipes have been impregnated with a water-based cleaner specifically formulated for manual degreasing of all metals by a simple wipe-on application at ambient temperatures as an easy, effective replacement for solvent-based products. The cleaner has mild rust-retarding properties, so steels and other metals sensitive to moisture will not readily corrode. It conforms to BS 7773 (1995) 3.2.3.B2 and DEF STAN 03/4 Process B.1.

BENEFITS

- Meets all current EPA PG6 Guidance Notes - no limitations on use.
- Easy to handle - effective cleaning for many surfaces.
- No flash point - no flammable restriction in normal factory use.
- High WEL Standard ingredients - low inhalation hazard.
- Mild odour - operator comfort.
- Works with all normal tap waters.

FLASHPOINT

None.

COVERAGE

The consumption of wipes will depend on the care in use and the condition of the surfaces to be cleaned. Practical evaluations have indicated that, when used as commended below, T Wipes 8 can - in cleaning effectiveness – more than equate to conventional solvent based cleaners.

APPLICATION

Normally, effective cleaning is achieved by simple wiping methods. The following notes may help to optimise the process whilst minimising needless waste:

1. Remove the lid to open the tub and feed the first wipes from the center of the roll through the center spout. Replace the lid and leave only sufficient wipe exposed to allow easy pull-through to draw out other wipes. Replace the cap to avoid premature drying of the wipes.



2. Folding the wipe to form a pad and progressively re-folding to use a clean area of the material, using both sides, will ensure maximum economy.
3. Before painting, remove traces of detergent by wiping with a clean damp cloth.
4. Partially used cloths can be stored in an airtight container (an old wipes tub would be suitable) and these can be used for initial cleaning of heavily contaminated surfaces.

DRYING

Most surfaces will be dry for painting within a few minutes. Should formed drying of the cleaned surface be necessary, temperature of up to 125°C may be used.

EQUIPMENT

Impervious gloves should be worn, as much to protect the skin from the oils and other residues removed from the surface as from the impregnant on the wipes. Inhalation protection is not normally required in areas of good factory ventilation.

ENVIRONMENTAL CONSIDERATIONS

T Wipes 8 contains VOCs (80 grams/litre or 240 grams/tub). Therefore, they meet the exemptions for low solvent cleaners for Emission Limits [e.g. for Metal & Plastic – PG6/23 (04) Table 9] and PG6/34 for compliance for Vehicle Refinishing [2004/42/11 B(a)(200)80]. Do not contain either Halogenated Hydrocarbons or PG6 'R' phrase chemicals. Used cloths should be disposed of as other oil-contaminated products.

SAFETY

Before use, refer to the Product Safety Data Sheet.

DISPOSAL

Dispose of in accordance with local authority requirements.

PRODUCT FAMILIES

The following products are referred to in this data sheet.



PRODUCT NAME	PRODUCT NUMBER
T WIPES 8	MP0304

Whilst every endeavour has been made to ensure that the information given in this data sheet is correct, PMD Chemicals Limited gives no warranty, express or implied, relating to the use or performance of this product.